FEATURE 460 – ATTENUATORS					
Roadway Side	**Offsets**	**LRS Package**	**Feature Type**	**Interlocking**	**Secured**
R/L	No	No	Point	Yes	Yes
Responsible Party for Data Collection		District Office of Maintenance			

Definition/Background: Attenuators are intended to provide a motor vehicle with a cushioned impact area prior to solid obstructions such as parapet walls, bridge columns, sign structures, and signal poles. They are generally constructed of modules or cells containing different types of energy absorption materials such as water, sand, or hex foam.

Lists the condition, date of inspection, installation date, repair date, comments, location, model number, attenuator type, and vehicle direction. All required information can be obtained from Type I and Type II inspection reports.

NOTE: *Attenuators require twice-yearly inspections, a Type 1 inspection in April and a Type 2 inspection in October. A Type 1 inspection is a visual inspection and a Type 2 inspection is an actual breakdown and cleaning of the attenuator. These inspections are typically performed by field crews and all information pertaining to these inspections may be input by the party performing the inspection or by the MMS personnel responsible for maintaining RCI after notification that the inspections are complete.*

NOTE: *If the below characteristics are located at a rest area, ramp, or other applicable sub-section, they are to be inventoried against the applicable sub-section number.*

ATCONDTN – ATTENUATOR CONDITION

HPMS	MIRE	Who/What uses this Information	Required For	Offset Direction	Offset Distance
N/A		Maintenance	All Active On and Active Exclusive roads, including managed lanes	N/A	N/A

How to Gather this Data: Use the following code that best describes the condition of the attenuator.

Codes	Descriptions	Codes	Descriptions
01	Good	**03**	Poor
02	Fair	**04**	Critical

ATINSPEC – ATTENUATOR INSPECTION DATE

HPMS	MIRE	Who/What uses this Information	Required For	Offset Direction	Offset Distance
N/A		Maintenance	All Active On and Active Exclusive roads, including managed lanes	N/A	N/A

How to Gather this Data: Code the date of latest attenuator inspection with leading zeros for months less than 10. No hyphens or backslash.

Value for Attenuator Inspection Date: 8 Bytes: MMDDYYYY

ATREPAIR – ATTENUATOR REPAIR DATEX

HPMS	MIRE	Who/What uses this Information	Required For	Offset Direction	Offset Distance
N/A		Maintenance	All Active On and Active Exclusive roads, including managed lanes	N/A	N/A

How to Gather this Data: Code the date attenuator repaired with leading zeros for months less than 10. No hyphens or backslash.

Value for Attenuator Inspection Date: 8 Bytes: MMDDYYYY

ATRMRKS1 – ATTENUATOR REMARKS – 1

HPMS	MIRE	Who/What uses this Information	Required For	Offset Direction	Offset Distance
N/A		Maintenance	All Active On and Active Exclusive roads, including managed lanes	N/A	N/A

How to Gather this Data: Code the statement concerning attenuator.

Value for Attenuator Remarks - 1: 20 Bytes: XXXXXXXXXXXXXXXXXXXX

ATRMRKS2 – ATTENUATOR REMARKS – 2

HPMS	MIRE	Who/What uses this Information	Required For	Offset Direction	Offset Distance
N/A		Maintenance	All Active On and Active Exclusive roads, including managed lanes	N/A	N/A

How to Gather this Data: Code the statement concerning attenuator.

NOTE: *New to the maintenance add screen.*

Value for Attenuator Remarks - 2: 20 Bytes: XXXXXXXXXXXXXXXXXXXX

ATTLOCCD – ATTENUATOR LOCATION CODE

HPMS	MIRE	Who/What uses this Information	Required For	Offset Direction	Offset Distance
N/A		Maintenance	All Active On and Active Exclusive roads, including managed lanes	N/A	N/A

How to Gather this Data: Use the following code that describes the location of the attenuator.

Codes	Descriptions	Codes	Descriptions	Codes	Descriptions
GL	Gore left	**LS**	Left shoulder	**RS**	Right shoulder
GR	Gore right	**MD**	Median		

ATTMODEL – ATTENUATOR MODEL NUMBER

HPMS	MIRE	Who/What uses this Information	Required For	Offset Direction	Offset Distance
N/A		Maintenance	All Active On and Active Exclusive roads, including managed lanes	N/A	N/A

How to Gather this Data: Code the model number given in the Attenuator Inventory and Inspection Procedure, Topic No. 850-055-003.

Value for Attenuator Model Number: 20 Bytes: XXXXXXXXXXXXXXXXXXXX

Model #	01 – Hi-Dro Cell (sandwich)
G	Color G-gray, Y-yellow, GN-green, BLK-black, BL-blue
209	Width of first diaphragm (2'-9")
508	Width of last diaphragm (5'-8")
S	S-standard or N-non-standard
8	Number of bays
S	S-wet or D-dry

Model #	02 – Hi-Dro Cell (cluster)
300	Width (3-0")
600	Length (6'0")
W	W-designates Hi-Dro cluster

Model #	03 – G-R-E-A-T System
200	Width of first diaphragm (2'-0")
200	Width of last diaphragm (2'-0")
S	S-standard or N-non-standard
F	
6	Number of bays

Model #	04/05 – Sand Crash Cushion (fitch or energite)
002	No. of 200 lb. Modules
004	No. of 400 lb. Modules
004	No. of 700 lb. Modules
0014	No. of 1400 lb. Modules
0021	No. of 2100 lb. Modules
F&E	Fitch & Energite (mixed installation)

Model #	06 – Hex Foam Sandwich
209	Width of first diaphragm (2'-9")
508	width of last diaphragm (5'-8")
H	
8	Number of bays
S	S-standard or N-non-standard

Model #	08 – QuadGurad System
QS	QS-QuadGuard System
24	Width of diaphragms (24")
5	Number of bays
G	Nose color, G-gray in Florida

Model #	09 – BREAKMASTER 350
106	There is only
106	one model number
BR	for this system.
S5	

10 – CAT 350
There is only one model number for this system.

Model #	11 – REACT 350
75	Design speed: 75, 62, 55, 45 mph
B	B-self-contained backup or S-side mounted anchors
036	Width (36")

Model #	12 – ADIEM 350
xx	Number of modules, 06 or 10

ATTYPECD – ATTENUATOR TYPE

HPMS	MIRE	Who/What uses this Information	Required For	Offset Direction	Offset Distance
N/A		Maintenance	All Active On and Active Exclusive roads, including managed lanes	N/A	N/A

How to Gather this Data: Use the code that describes the attenuator type.

Code	Type	Code	Type	Code	Type
01	Hi-Dro Cell (sandwich)	**08**	QuadGuard System	**15**	TAU-II
02	Hi-Dro Cell (cluster)	**09**	BRAKEMASTER 350	**16**	QuadGuard Elite
03	G-R-E-A-T System	**10**	CAT 350	**17**	Smart Cushion
04	Sand Crash Cushion (fitch)	**11**	REACT 350	**18**	Easi-Cell
05	Sand Crash Cushion (energite)	**12**	ADIEM 350	**19**	X-MAS
06	Hex Foam Sandwich	**13**	DRAG-NET	**20**	QuadGuard II
07	Other	**14**	TRACC		

Examples:

02 – Hi-Dro Cell (cluster)

03 – G-R-E-A-T System

05 – Sand Crash Cushion (energite)

06 – Hex Foam Sandwich

08 – QuadGuard System

12 – ADIEM 350

13 – DRAG-NET

14 – TRACC

15 – TAU-II

16 – QuadGuard Elite

Examples cont.

17 – Smart Cushion

18 – Easi-Cell

19 – X-MAS

20 – QuadGuard II

ATTYPINS – ATTENUATOR INSPECTION TYPE

HPMS	MIRE	Who/What uses this Information	Required For	Offset Direction	Offset Distance
N/A		Maintenance	All Active On and Active Exclusive roads, including managed lanes	N/A	N/A

How to Gather this Data: Use the following code that describes the attenuator inspection type.

Codes	Descriptions	Codes	Descriptions
01	Type 1 inspection	**02**	Type 2 inspection

VEHDIRCD – GENERAL VEHICULAR DIRECTION

HPMS	MIRE	Who/What uses this Information	Required For	Offset Direction	Offset Distance
N/A		Maintenance	All Active On and Active Exclusive roads, including managed lanes	N/A	N/A

How to Gather this Data: Use the code that describes the vehicle direction.

Codes	Descriptions	Codes	Descriptions
NB	Northbound	**EB**	Eastbound
SB	Southbound	**WB**	Westbound